

Triton 4000 High Bond PS Adhesive

TECHNICAL DATA SHEET

DESCRIPTION:

Triton 4000 Pressure Sensitive Adhesive is low in VOC and is also anti microbial. It has been developed for the installation of vinyl composition tiles. It is also suitable for the installation of Carpet Tiles & slab underlay's used in the double bond carpet installation.

SURFACE PREPARATION:

All surfaces to be bonded should be dry, smooth, and free of any contaminants that may affect final bond. All surfaces must be prepared in accordance with current Australian Standards 1884 Floor Coverings Resilient Sheet including moisture testing. It is recommended that all highly absorbent sub floors be primed with **suitable Acrylic Floor & Wall Primer** prior to the application of adhesive. The minimum sub floor temperature prior to commencing preparation or adhesive application is 10°C.

STANDARDS

Australian/NZ Standard 1884-2012
Australian/NZ Standard 2455.1.2007
Australian/NZ Standard 2455.2.2007

DIRECTION FOR USE:

For the installation of composition tiles & textured backed double bond underlays, apply adhesive using a 1.6mm x 1.6mm x 1.6mm "V" notched spreader with approx coverage of 5m² per litre for. When installing carpet tiles and smooth backed double bond underlay, use a long nap roller with approx coverage of 7m² per litre. Adhesive should be allowed to clear prior to floor covering being placed into the adhesive film. Clear is when the adhesive changes from white wet adhesive to dry clear tacky film of adhesive. Clear time will depend on atmospheric conditions. Complete installation according to manufacture instruction. Roll installation on completion with the recommended weight roller. Do not allow heavy traffic for 24 hours.

CLEAN UP:

Clean tools immediately after use with warm soapy water. Dried adhesive may be softened from tools using a suitable solvent.

TYPICAL PROPERTIES:

- Base: Acrylic
- Solids: Approx 50%
- Shelf Life: 12 months in sealed container at 20°C
- Packaging: 15 Litre pails

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on request.