GSA CORNICE ADHESIVE 60 MIN

Description
A specially formulated adhesive for fixing cornice to plasterboard walls & ceilings. It has a working life of 60 minutes.

Features & Benefits
- Quick grab
- High strength
- 60-minute working time
- Clean up with water

Preparation
Mark out & cut the cornice to the exact length using a mitre box.

Mixing
Place 1 litre of water in container & sprinkle in approximately 2kg of GSA Cornice Adhesive.
Mix thoroughly to a creamy consistency. Do not mix more than can be used within 50 minutes.

Application
Apply GSA Cornice Adhesive in a 10mm wide bead along the back edges of the cornice. Each piece should be coated and fixed separately starting with the shorter lengths. Press the cemented cornice into the walls & ceiling angle, extruding the surplus cement. Hold in position with temporary nails. Remove the surplus cement with a small broad knife and clean with a damp cloth or sponge. Use surplus cement to fill & smooth off mitres.

Coverage
5kg is required for 42 metres of cornice.

Clean up
Wash thoroughly with water after handling.

Storage
Seal bag when not in use. Store in a cool, dry place.

First Aid
Please refer to the Safety Data Sheet which is available at www.cwbrands.com.au/

Disclaimer
CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and is to the best of our knowledge true and accurate. The user must ensure of the product(s) in their application prior to use in particular to determine its performance, efficiency and safety. The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Products conform solely to the information contained in this and other related CW Brands Pty Ltd publications.
CW Brands Pty Ltd reserves the right to make changes to specifications and information related to the products at any time. Users are asked to check that the literature in their possession is the latest issue. Statements contained herein should not be considered as a warranty of any kind, expressed or implied in describing the performance or suitability of the product for a particular application. No liability is accepted for infringement of any patents or any other intellectual property right.

