keratrade

Tack is a high performance, solvent-free pressure sensitive adhesive for resilient synthetic floor and wallcoverings for interior areas.

Tack

Pressure Sensitive Flooring Adhesive



Suitable for:

- Rubber flooring sheet, PVC sport flooring sheet, vinyl tile and cushioned vinyl coverings, inc, those with textile fleece backings.
- <5g/L VOC

Suitable for textile coverings with synthetic backings, foam, latex, fleece, woven goods, needle punch, and natural fibre carpets.

APPLICATION FLEXIBILITY:
Adhesive can be applied with a roller or notched trowels ("V1" or "V2"), depending on the bond strength and application requirements.

CLEAR DRYING ADHESIVE:
Dries clear to minimize transfer to carpet backs, allowing for easy repositioning or re-laying.

Work time:	15–20 min
Foot Traffic:	12 Hrs
Normal use:	24 Hrs
Full Strength:	3 Days
App Temp:	10°C – 35°C
Size:	15KG

Coverage:

- 150m² @ 10mm Nap Roller
- 75m² @ 1mm V Trowel
- 45m² @ 2mm V Trowel

Build Green

BuildGreen
SUSTAINABLE MATERIALS. PROVEN PERFORMANCE.

1300 NO HARM (664 276)

sales@buildgreen.au
www.buildgreen.au